

SAFETY DATA SHEET

according to the Global Harmonized System (and with all of the information required by the HPR)

Revision Date 09/05/2018

Version 1.4

SECTION 1. Identification**Product identifier**

Product number	BX1791
Product name	<i>iso</i> -Butyl Alcohol GR ACS
CAS-No.	78-83-1

Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Reagent for analysis
-----------------	----------------------

Details of the supplier of the safety data sheet

Company	Millipore (Canada) Ltd 109 Woodbine Downs Blvd. Unit 5 Etobicoke Ontario M9W 6Y1 Canada General Inquiries: +1 800-645-5476 Monday to Friday, 9:00 AM to 4:00 PM Eastern Time (GMT-5) MilliporeSigma is a business of Merck KGaA, Darmstadt, Germany.
---------	---

Emergency telephone	800-424-9300 CHEMTREC (USA) +1-703-527-3887 CHEMTREC (International) 24 Hours/day; 7 Days/week
---------------------	--

SECTION 2. Hazards identification**GHS Classification**

Flammable liquid, Category 3, H226
Skin irritation, Category 2, H315
Serious eye damage, Category 1, H318
Specific target organ systemic toxicity - single exposure, Category 3, Respiratory system, Central nervous system, H335 H336

For the full text of the H-Statements mentioned in this Section, see Section 16.

GHS-Labeling*Hazard pictograms**Signal Word*

Danger

Hazard Statements

H226 Flammable liquid and vapor.
H315 Causes skin irritation.

SAFETY DATA SHEET

according to the Global Harmonized System (and with all of the information required by the HPR)

Product number

BX1791

Version 1.4

Product name

iso-Butyl Alcohol GR ACS

H318 Causes serious eye damage.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.

Precautionary Statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.
P321 Specific treatment (see supplemental first aid instructions on this label).
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.
P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. Composition/information on ingredients

Formula	(CH ₃) ₂ CHCH ₂ OH	C ₄ H ₁₀ O (Hill)
Molar mass	74.12 g/mol	

Hazardous ingredients

Chemical name (Concentration)
CAS-No.
iso-butanol (>= 90 % - <= 100 %)
78-83-1

SECTION 4. First aid measures

Description of first-aid measures

SAFETY DATA SHEET

according to the Global Harmonized System (and with all of the information required by the HPR)

Product number

BX1791

Version 1.4

Product name

iso-Butyl Alcohol GR ACS

Inhalation

After inhalation: fresh air. Call in physician.

Skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/shower.

Eye contact

After eye contact: rinse out with plenty of water. Immediately call in ophthalmologist. Remove contact lenses.

Ingestion

After swallowing: caution if victim vomits. Risk of aspiration! Keep airways free. Pulmonary failure possible after aspiration of vomit. Call a physician immediately.

Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed

Irritation and corrosion, somnolence, Drowsiness, Cough, Shortness of breath

Risk of serious damage to eyes.

respiratory paralysis, Dizziness, Unconsciousness, narcosis, inebriation, Headache, Coma

Risk of corneal clouding.

Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂), Foam, Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

Special hazards arising from the substance or mixture

Combustible.

Vapors are heavier than air and may spread along floors.

Forms explosive mixtures with air at elevated temperatures.

Development of hazardous combustion gases or vapors possible in the event of fire.

Advice for firefighters

Special protective equipment for fire-fighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

SAFETY DATA SHEET

according to the Global Harmonized System (and with all of the information required by the HPR)

Product number

BX1791

Version 1.4

Product name

iso-Butyl Alcohol GR ACS

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert.

Advice for emergency responders:

Protective equipment see section 8.

Environmental precautions

Do not let product enter drains. Risk of explosion.

Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

SECTION 7. Handling and storage

Precautions for safe handling

Observe label precautions.

Work under hood. Do not inhale substance/mixture. Avoid generation of vapors/aerosols.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

Store at room temperature.

SECTION 8. Exposure controls/personal protection

Exposure limit(s)

Ingredients

Basis	Value	Threshold limits	Remarks
<i>iso-butanol 78-83-1</i>			
CAD AB OEL	Time Weighted Average (TWA):	50 ppm 152 mg/m ³	
CAD BC OEL	Time Weighted Average (TWA):	50 ppm	
CAD MB OEL	Time Weighted Average (TWA):	50 ppm	
CAD ON OEL	Time Weighted Average (TWAEV):	50 ppm	
OEL (QUE)	Time Weighted Average (TWA):	50 ppm 152 mg/m ³	

Engineering measures

Technical measures and appropriate working operations should be given priority over the use of personal protective equipment.

SAFETY DATA SHEET

according to the Global Harmonized System (and with all of the information required by the HPR)

Product number

BX1791

Version 1.4

Product name

iso-Butyl Alcohol GR ACS

Individual protection measures

Protective clothing should be selected specifically for the workplace, depending on concentration and quantity of the hazardous substances handled. The chemical resistance of the protective equipment should be inquired at the respective supplier.

Hygiene measures

Immediately change contaminated clothing. Apply skin- protective barrier cream. Wash hands and face after working with substance.

Eye/face protection

Tightly fitting safety goggles

Hand protection

full contact:

Glove material:	Nitrile rubber
Glove thickness:	0.40 mm
Break through time:	480 min

splash contact:

Glove material:	Nitrile rubber
Glove thickness:	0.11 mm
Break through time:	10 min

The protective gloves to be used must comply with the specifications of EC Directive 89/686/EEC and the related standard EN374, for example KCL 730 Camatril® -Velours (full contact), KCL 741 Dermatril® L (splash contact).

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types.

This recommendation applies only to the product stated in the safety data sheet and supplied by us as well as to the purpose specified by us. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Other protective equipment:

Flame retardant antistatic protective clothing.

Respiratory protection

required when vapors/aerosols are generated.

Recommended Filter type: Filter A (acc. to DIN 3181) for vapors of organic compounds

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are performed according to the instructions of the producer. These measures have to be properly documented.

SECTION 9. Physical and chemical properties

Physical state	liquid
Color	colorless
Odor	alcohol-like
Odor Threshold	0.001 - 73.0 ppm

SAFETY DATA SHEET

according to the Global Harmonized System (and with all of the information required by the HPR)

Product number

BX1791

Version 1.4

Product name

iso-Butyl Alcohol GR ACS

pH	7 at 80 g/l 68 °F (20 °C)
Melting point	-162 °F (-108 °C)
Boiling point/boiling range	223 - 226 °F (106 - 108 °C) at 1,013 hPa Method: DIN 53171
Flash point	82 °F (28 °C) Method: c.c.
Evaporation rate	No information available.
Flammability (solid, gas)	No information available.
Lower explosion limit	1.5 %(V)
Upper explosion limit	12 %(V)
Vapor pressure	12 hPa at 68 °F (20 °C)
Relative vapor density	2.55
Density	0.802 g/cm ³ at 68 °F (20 °C)
Relative density	No information available.
Water solubility	85 g/l at 68 °F (20 °C)
Partition coefficient: n-octanol/water	log Pow: 0.79 (25 °C) OECD Test Guideline 107 Bioaccumulation is not expected.
Autoignition temperature	No information available.
Decomposition temperature	No information available.
Viscosity, dynamic	4 mPa.s at 68 °F (20 °C)
Explosive properties	Not classified as explosive.
Oxidizing properties	none

SAFETY DATA SHEET

according to the Global Harmonized System (and with all of the information required by the HPR)

Product number

BX1791

Version 1.4

Product name

iso-Butyl Alcohol GR ACS

Ignition temperature

806 °F (430 °C)

Method: DIN 51794

SECTION 10. Stability and reactivity

Reactivity

Vapor/air-mixtures are explosive at intense warming.

Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

Possibility of hazardous reactions

Exothermic reaction with:

Acid chlorides, strong reducing agents

Risk of ignition or formation of inflammable gases or vapors with:

chromium(VI) oxide, Strong oxidizing agents, Aluminum

Violent reactions possible with:

Alkali metals, Alkaline earth metals

Conditions to avoid

Heating.

Incompatible materials

Aluminum, rubber, various plastics

Hazardous decomposition products

no information available

SECTION 11. Toxicological information

Information on toxicological effects

Likely route of exposure

Inhalation, Eye contact, Skin contact

Acute oral toxicity

LD50 Rat: > 2,830 mg/kg

OECD Test Guideline 401

Symptoms: Irritations of mucous membranes in the mouth, pharynx, oesophagus and gastrointestinal tract., Risk of aspiration upon vomiting., Aspiration may cause pulmonary edema and pneumonitis.

Acute inhalation toxicity

LC50 Rat: 24.6 mg/l; 4 h ; vapor

(IUCLID)

Irritating to respiratory system.

SAFETY DATA SHEET

according to the Global Harmonized System (and with all of the information required by the HPR)

Product number

BX1791

Version 1.4

Product name

iso-Butyl Alcohol GR ACS

Symptoms: mucosal irritations, Cough, Shortness of breath, Possible damages:, damage of respiratory tract

Acute dermal toxicity

LD50 Rat: 2,460 mg/kg

OECD Test Guideline 402

Skin irritation

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

Causes skin irritation.

Eye irritation

Risk of corneal clouding.

Causes serious eye damage.

Genotoxicity in vitro

Ames test

Salmonella typhimurium

Result: negative

(National Toxicology Program)

Specific target organ systemic toxicity - single exposure

May cause respiratory irritation.

Target Organs: Respiratory system

May cause drowsiness or dizziness.

Target Organs: Central nervous system

Specific target organ systemic toxicity - repeated exposure

The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Aspiration hazard

Regarding the available data the classification criteria are not fulfilled.

Carcinogenicity

IARC

No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

ACGIH

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

Further information

After absorption:

SAFETY DATA SHEET

according to the Global Harmonized System (and with all of the information required by the HPR)

Product number

BX1791

Version 1.4

Product name

iso-Butyl Alcohol GR ACS

Headache, Dizziness, inebriation, Unconsciousness, narcosis

After uptake of large quantities:

Coma, respiratory paralysis

Other dangerous properties can not be excluded.

Handle in accordance with good industrial hygiene and safety practice.

SECTION 12. Ecological information

Ecotoxicity

Toxicity to fish

LC50 Pimephales promelas (fathead minnow): 1,430 mg/l; 96 h (IUCLID)

Toxicity to daphnia and other aquatic invertebrates

EC5 E.sulcatum: 295 mg/l; 72 h (Lit.)

EC50 Daphnia magna (Water flea): 1,439 mg/l; 48 h

DIN 38412 (IUCLID)

Toxicity to algae

IC50 Desmodesmus subspicatus (green algae): 1,250 mg/l; 48 h (IUCLID)

Toxicity to bacteria

EC50 Photobacterium phosphoreum: 1,225 mg/l; 15 min (IUCLID)

Persistence and degradability

Biodegradability

99 %; 14 d

OECD Test Guideline 301A

Readily biodegradable.

> 90 %; 5 d

OECD Test Guideline 302B

Readily eliminated from water

Chemical Oxygen Demand (COD)

2,600 mg/g

(External MSDS)

Theoretical oxygen demand (ThOD)

2,600 mg/g

(Lit.)

Ratio BOD/ThBOD

BOD5 64 %

(Lit.)

Ratio COD/ThBOD

100 %

(Lit.)

Bioaccumulative potential

Partition coefficient: n-octanol/water

log Pow: 0.79 (25 °C)

OECD Test Guideline 107

Bioaccumulation is not expected.

Mobility in soil

No information available.

SAFETY DATA SHEET

according to the Global Harmonized System (and with all of the information required by the HPR)

Product number

BX1791

Version 1.4

Product name

iso-Butyl Alcohol GR ACS

SECTION 13. Disposal considerations

The information presented only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations. Disposal should be in accordance with applicable regional, national and local laws and regulations.

SECTION 14. Transport information

Land transport (DOT)

UN number	UN 1212
Proper shipping name	ISOBUTANOL
Class	3
Packing group	III
Environmentally hazardous	--

Air transport (IATA)

UN number	UN 1212
Proper shipping name	ISOBUTANOL
Class	3
Packing group	III
Environmentally hazardous	--
Special precautions for user	no

Sea transport (IMDG)

UN number	UN 1212
Proper shipping name	ISOBUTANOL
Class	3
Packing group	III
Environmentally hazardous	--
Special precautions for user	yes
EmS	F-E S-D

SECTION 15. Regulatory information

United States of America

Canada

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

Notification status

TSCA: All components of the product are listed in the TSCA-inventory.

DSL: All components of this product are on the Canadian DSL

SAFETY DATA SHEET

according to the Global Harmonized System (and with all of the information required by the HPR)

Product number

BX1791

Version 1.4

Product name

iso-Butyl Alcohol GR ACS

SECTION 16. Other information

Training advice

Provide adequate information, instruction and training for operators.

Labeling

Hazard pictograms



Signal Word

Danger

Hazard Statements

H226 Flammable liquid and vapor.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

Precautionary Statements

Prevention

P210 Keep away from heat.

P280 Wear eye protection.

Response

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P313 Get medical advice/ attention.

Key or legend to abbreviations and acronyms used in the safety data sheet

Used abbreviations and acronyms can be looked up at www.wikipedia.org.

Revision Date 09/05/2018

The information contained herein is based on the present state of our knowledge. It characterizes the product with regard to appropriate safety precautions. It does not represent a warranty of any product properties and we assume no liability for any loss or injury which may result from the use of this information. Users should conduct their own investigations to determine the suitability of the information.

All rights reserved. Millipore and the "M" Mark are registered trademarks of Merck KGaA, Darmstadt, Germany.