CG2 Page 1 of 7

Bundaberg White Crystalline Sugar

Hazard Alert Code: LOW

(Chemwatch name: BUNDABERG WHITE CRYSTALLINE SUGAR)

Chemwatch Material Safety Data Sheet Version No: 2.0 Chemwatch 87020

Issue Date: 6-Dec-2007 CD 2011/1

NC317TCP

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

Bundaberg White Crystalline Sugar

SYNONYMS

"white sugar'

PRODUCT USE

Ingredient in food and food preparations.

Company: Bundaberg Sugar Ltd

Address:

Level 1, 155 Wharf Street

Spring Hill QLD, 4000 Australia

Telephone: +61 7 3835 8400 Fax: +61 7 3835 8411

Section 2 - HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE

NON-HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS. According to NOHSC Criteria, and ADG Code.

CHEMWATCH HAZARD RATINGS

Min Max Flammability: 1 Toxicity: 0 **Body Contact:** 1 Min/Nil=0 Low=1 0 Reactivity: Moderate=2 High=3 Chronic: Extreme=4

POISONS SCHEDULE

None

RISK SAFETY

None under normal operating conditions. None under normal operating conditions.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS RN % NAME 57-50-1 sucrose >99

Section 4 - FIRST AID MEASURES

SWALLOWED

- Immediately give a glass of water.
- First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

EYE

- If this product comes in contact with the eyes:
- · Wash out immediately with fresh running water.

CG₂ Page 2 of 7

Bundaberg White Crystalline Sugar

Hazard Alert Code: LOW

(Chemwatch name: BUNDABERG WHITE CRYSTALLINE SUGAR)

Chemwatch Material Safety Data Sheet

Version No: 2.0

Chemwatch 87020

CD 2011/1 Issue Date: 6-Dec-2007

NC317TCP

- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally
- Seek medical attention without delay; if pain persists or recurs seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

- If skin or hair contact occurs:
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- If dust is inhaled, remove from contaminated area.
- Encourage patient to blow nose to ensure clear passage of breathing.
- If irritation or discomfort persists seek medical attention.

NOTES TO PHYSICIAN

■ Treat symptomatically.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Water spray or fog.
- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water courses.
- Use water delivered as a fine spray to control fire and cool adjacent area.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

FIRE/EXPLOSION HAZARD

■ Combustible.

Avoid creating dust - may present dust explosion hazard. Dry dust can be electrostatically charged by turbulence, pneumatic transport, pouring, in exhaust ducts and during transport. Build-up of electrostatic charge may be prevented by grounding. Combustion products include: carbon monoxide (CO) and carbon dioxide (CO2).

FIRE INCOMPATIBILITY

■ Avoid contamination with strong oxidising agents as ignition may result.

HAZCHEM

None

PERSONAL PROTECTION

Glasses: Gloves: Respirator: Not normally required. When handling larger quantities: Particulate

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid contact with skin and eyes.
- Control personal contact by using protective equipment.
- Use dry clean up procedures and avoid generating dust.
- Place in a suitable, labelled container for waste disposal.

MAJOR SPILLS

- Remove all ignition sources.
- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.

CG₂ Page 3 of 7

Bundaberg White Crystalline Sugar

Hazard Alert Code: LOW

(Chemwatch name: BUNDABERG WHITE CRYSTALLINE SUGAR)

Chemwatch Material Safety Data Sheet

Version No: 2.0

Chemwatch 87020

CD 2011/1 Issue Date: 6-Dec-2007

NC317TCP

- Control personal contact by using protective equipment and dust respirator.
- Prevent spillage from entering drains, sewers or water courses.
- Avoid generating dust.
- Sweep, shovel up. Recover product wherever possible.
- Put residues in labelled plastic bags or other containers for disposal.
- If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Remove all ignition sources.
- Limit all unnecessary personal contact.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- When handling DO NOT eat, drink or smoke.
- Always wash hands with soap and water after handling.
- Avoid physical damage to containers.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.

SUITABLE CONTAINER

■ Multi-ply paper bag with sealed plastic liner or heavy gauge plastic bag.

NOTE: Bags should be stacked, blocked, interlocked, and limited in height so that they are stable and secure against sliding or collapse. Check that all containers are clearly labelled and free from leaks. Packing as recommended by manufacturer.

STORAGE INCOMPATIBILITY

Avoid storage with oxidisers.

STORAGE REQUIREMENTS

- Keep dry.
- Store under cover.
- Store in a well ventilated area.
- Store away from sources of heat or ignition.
- Observe manufacturer's storing and handling recommendations.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



- X: Must not be stored together
- O: May be stored together with specific preventions
- +: May be stored together

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m³	STEL ppm	STEL mg/m³	Peak ppm	Peak mg/m³	TWA F/CC	Notes
Australia Exposure Standards	sucrose (Sucrose (a))		10						(see Chapter 14)

MATERIAL DATA

BUNDABERG WHITE CRYSTALLINE SUGAR:

Not available

SUCROSE:

■ It is the goal of the ACGIH (and other Agencies) to recommend TLVs (or their equivalent) for all substances for which there is

CG₂ Page 4 of 7

Bundaberg White Crystalline Sugar



(Chemwatch name: BUNDABERG WHITE CRYSTALLINE SUGAR)

Chemwatch Material Safety Data Sheet

Version No: 2.0

Chemwatch 87020

Issue Date: 6-Dec-2007 CD 2011/1

NC317TCP

evidence of health effects at airborne concentrations encountered in the workplace.

At this time no TLV has been established, even though this material may produce adverse health effects (as evidenced in animal experiments or clinical experience). Airborne concentrations must be maintained as low as is practically possible and occupational exposure must be kept to a minimum.

NOTE: The ACGIH occupational exposure standard for Particles Not Otherwise Specified (P.N.O.S) does NOT apply.

Sucrose has little adverse effect on the lung and does not produce significant organic disease. Massive doses are necessary to produce systemic toxicity. A Finnish study concluded that exposures below 5 mg/m3 should protect dental health, provided worker ingestion of the product was controlled. This finding was prompted by concerns within the bakery and confectionery industry of a connection between sucrose exposure and dental caries.

PERSONAL PROTECTION



- No special equipment for minor exposure i.e. when handling small quantities.
- OTHERWISE:
- Safety glasses with side shields.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59]

■ No special equipment needed when handling small quantities.

OTHERWISE: Wear chemical protective gloves, eg. PVC.

■ No special equipment needed when handling small quantities.

OTHERWISE:

- Overalls.
- Barrier cream.
- Evewash unit

RESPIRATOR

Protection Factor Half-Face Respirator Full-Face Respirator Powered Air Respirator 10 x ES P1 Air-line* PAPR-P1 -50 x FS Air-line** P2 PAPR-P2 100 x ES P3 Air-line*

PAPR-P3 Air-line*

* - Negative pressure demand ** - Continuous flow.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required. For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

- Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively large, a certain proportion will be powdered by mutual friction.
- Exhaust ventilation should be designed to prevent accumulation and recirculation of particulates in the workplace.
- If in spite of local exhaust an adverse concentration of the substance in air could occur, respiratory protection should be considered. Such protection might consist of:
- (a): particle dust respirators, if necessary, combined with an absorption cartridge;
- (b): filter respirators with absorption cartridge or canister of the right type;
- (c): fresh-air hoods or masks
- Build-up of electrostatic charge on the dust particle, may be prevented by bonding and grounding.
- Powder handling equipment such as dust collectors, dryers and mills may require additional protection measures such as

Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to efficiently remove the contaminant.


Air Speed: Type of Contaminant:

direct spray, spray painting in shallow booths, drum filling,

http://full.chemwatch.net/cg2/msds.exe?fontsize=&print=Y&rCode=&prefname=&con... 1/04/2011

CG2 Page 5 of 7

Bundaberg White Crystalline Sugar



(Chemwatch name: BUNDABERG WHITE CRYSTALLINE SUGAR)

Chemwatch Material Safety Data Sheet Version No: 2.0 Chemwatch 87020

Issue Date: 6-Dec-2007 CD 2011/1

NC317TCP

conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)

grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of

very high rapid air motion).

Within each range the appropriate value depends on:

Lower end of the range 1: Room air currents minimal or favourable to capture

2: Contaminants of low toxicity or of nuisance value only

3: Intermittent, low production.

4: Large hood or large air mass in motion

1-2.5 m/s (200-500 f/min.)

2.5-10 m/s (500-2000 f/min.)

Upper end of the range

1: Disturbing room air currents

2: Contaminants of high toxicity

3: High production, heavy use

4: Small hood-local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 4-10 m/s (800-2000 f/min) for extraction of crusher dusts generated 2 metres distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

 (\mathcal{C})

(°C)

APPEARANCE

White crystals; soluble in water.

PHYSICAL PROPERTIES

Solid.

Mixes with water.

Divided Molecular State solid Weight Melting Boiling 160-Range Range 186 (\mathcal{C}) (\mathcal{C})

Solubility

Vapour

Density

Miscible water (g/L)

Not .(1% available solution)

pH (as Not applicable supplied)

Vapour Not Pressure applicable (kPa) Specific

Gravity 1.59 (water=1) Relative

(air=1) Evaporation Not Rate applicable 342.34

Not available

Flash Not Point applicable

Decomposition Not Temp available

Autoignition Not Temp available (°C)

Upper Explosive Not Limit available (%)

Lower Explosive 0.045 Limit g/l (%)

Volatile Not Component applicable (%vol)

Section 10 - CHEMICAL STABILITY

CONDITIONS CONTRIBUTING TO INSTABILITY

Not

applicable

Presence of incompatible materials

CG₂ Page 6 of 7

Bundaberg White Crystalline Sugar

Hazard Alert Code: LOW

(Chemwatch name: BUNDABERG WHITE CRYSTALLINE SUGAR)

Chemwatch Material Safety Data Sheet Version No: 2.0 Chemwatch 87020

CD 2011/1 Issue Date: 6-Dec-2007

NC317TCP

- · Product is considered stable.
- Hazardous polymerisation will not occur.

For incompatible materials - refer to Section 7 - Handling and Storage.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

■ The solid/dust is non-toxic if swallowed.

Considered an unlikely route of entry in commercial/industrial environments.

EYE

■ The dust may produce eye discomfort causing smarting, pain and redness.

SKIN

■ The material may be slightly discomforting to the skin if exposure is prolonged or from repeated exposures over long periods.

INHALED

■ Not normally a hazard due to non-volatile nature of product.

The dust may be discomforting to the upper respiratory tract.

Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled.

If prior damage to the circulatory or nervous systems has occurred or if kidney damage has been sustained, proper screenings should be conducted on individuals who may be exposed to further risk if handling and use of the material result in excessive exposures.

CHRONIC HEALTH EFFECTS

■ Principal routes of exposure are by accidental skin and eye contact and inhalation of generated dusts.

TOXICITY AND IRRITATION

BUNDABERG WHITE CRYSTALLINE SUGAR:

■ None assigned. Refer to individual constituents.

SUCROSE:

■ unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY IRRITATION Oral (rat) LD50: 29700 mg/kg Nil Reported

Intraperitoneal (Mouse) LD50: 14000 mg/kg Oral (Human) TDLo: 9.6E-5 mg/kg

Section 12 - ECOLOGICAL INFORMATION

SUCROSE:

log Pow (Verschueren 1983): -3.67

ThOD: 1.12

ThOD: 1.12

sucrose

Ecotoxicity

Persistence: Persistence: Bioaccumulation Ingredient Mobility

Water/Soil Air LOW LOW **HIGH**

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Authority for disposal.
- Bury or incinerate residue at an approved site.
- Recycle containers if possible, or dispose of in an authorised landfill.

CG₂ Page 7 of 7

Bundaberg White Crystalline Sugar

Hazard Alert Code: LOW

(Chemwatch name: BUNDABERG WHITE CRYSTALLINE SUGAR)

Chemwatch Material Safety Data Sheet

Version No: 2.0

Chemwatch 87020

Issue Date: 6-Dec-2007

CD 2011/1

NC317TCP

Section 14 - TRANSPORTATION INFORMATION

HAZCHEM:

None (ADG7)

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS: ADG7, UN, IATA, IMDG

Section 15 - REGULATORY INFORMATION

POISONS SCHEDULE

None

REGULATIONS

Regulations for ingredients

sucrose (CAS: 57-50-1) is found on the following regulatory lists;

"Australia Exposure Standards", "Australia Inventory of Chemical Substances (AICS)", "China (Hong Kong) Occupational Exposure Limits", "China Inventory of Existing Chemical Substances", "Indonesia Threshold Limit Value for chemical substances in the workplace (Bahasa Indonesian)","International Fragrance Association (IFRA) Survey: Transparency List","Korea (South) Existing Chemicals List (KECL)","Korea (South) Occupational Exposure Standards (Korean)","Korea (South) Occupational Exposure Standards (Respirable microdust / Total dust) (Korean)","Korea GHS","Malaysia Permissible Exposure Limits","New Zealand Inventory of Chemicals (NZIoC)","New Zealand Workplace Exposure Standards (WES)","OECD Representative List of High Production Volume (HPV) Chemicals", "Philippines Inventory of Chemicals and Chemical Substances (PICCS)", "Singapore Permissible Exposure Limits of Toxic Substances"

No data for Bundaberg White Crystalline Sugar (CW: 87020)

Section 16 - OTHER INFORMATION

- Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references. A list of reference resources used to assist the committee may be found at:
- The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: 6-Dec-2007 Print Date:1-Apr-2011