

# POWERHOLD 3500 ULTRA PREMIUM CARPET ADHESIVE

# MATERIAL SAFETY DATA SHEET

#### SECTION I PRODUCT IDENTIFICATION

Manufactured for: Floor Covering Distributor Alliance

Emergency Phone: 864-967-7691

PRODUCT NAME: POWERHOLD 3500 Ultra Premium

Carpet Adhesive

CHEMICAL FAMILY: Water Base Adhesive

# SECTION II HAZARDOUS INGREDIENTS AND EXPOSURE LIMITS

Chemical Name - None

### SECTION III HAZARDS IDENTIFICATION

PRIMARY ROUTES OF ENTRY: Eyes.

MEDICAL CONDITIONS AGGRAVATED BY

EXPOSURE: None known.

POTENTIAL HEALTH EFFECTS:

EYE CONTACT: May cause slight irritation. SKIN CONTACT: May cause slight irritation.

INGESTION: No effects known. INHALATION: No effect known.

CHRONIC: None known.

CARCINOGENICITY: This product contains no known

carcinogen listed by IARC, NTP, or OSHA.

### SECTION IV FIRST AID MEASURES

EYE CONTACT: Flush with water for 15 minutes.

Contact a physician if irritation occurs.

SKIN CONTACT: Wash with soap and water. INGESTION: Do not induce vomiting. Contact a

physician.

# SECTION V FIRE-FIGHTING MEASURES

FLASH POINT (°)F: None.

LOWER FLAMMABLE LIMIT: None. UPPER FLAMMABLE LIMIT: None.

FIRE-FIGHTING INSTRUCTIONS: Use protective

clothing and self-contained breathing apparatus.

EXTINGUISHING MEDIA: Water fog, CO<sub>2</sub>, dry chemical,

and chemical foam.

DECOMPOSITION PRODUCTS: Dried material may produce CO, CO<sub>2</sub>, NO<sub>x</sub>, and other products from the

burning of aromatic hydrocarbons.

### SECTION VI ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Dispense sand, sawdust, or vermiculite. Collect and place in waste container. Wash area thoroughly with water.

#### SECTION VII HANDLING AND STORAGE

HANDLING: Use good hygienic practices. (Wash hands

before eating, using washroom, or smoking.)

Keep out of the reach of children. STORAGE: Store above 40°F.

# SECTION VIII EXPOSURE CONTROLS/PERSONAL PROTECTION

PERSONAL PROTECTIVE EQUIPMENT:

EYE/FACE PROTECTION: Splash goggles.

SKIN PROTECTION: Gloves.

RESPIRATORY PROTECTION: Not normally

required with good ventilation.

ENGINEERING CONTROLS: Normal room ventilation.

# SECTION IX PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT (°F): 212

SPECIFIC GRAVITY (WATER = 1): 1.2 VAPOR PRESSURE: Same as water. VAPOR DENSITY(air=1): Same as water.

% VOLATILE BY WEIGHT: 34.0

pH: 9.85

APPEARANCE AND ODOR: Light straw colored paste. GRAMS VOLATILE ORGANIC COMPOUNDS/LITER

OF MATERIAL: 0 (Calculated)

### SECTION X STABILITY AND REACTIVITY

CHEMICAL STABILITY: Stable.
POLYMERIZATION: Will not occur.
CONDITIONS TO AVOID: None known.

HAZARDOUS DECOMPOSITION PRODUCTS: None.

### SECTION XI TOXICOLOGICAL INFORMATION

No Information available.

### SECTION XII ECOLOGICAL INFORMATION

No information available.

# **SECTION XIII DISPOSAL CONSIDERATIONS**

Dispose of in accordance with Federal, State and Local regulations.

# SECTION XIV TRANSPORT INFORMATION

For domestic transportation purpose, this product is not designated as a hazardous material by the U.S. Department Of Transportation.



# POWERHOLD 3500 ULTRA PREMIUM CARPET ADHESIVE

# MATERIAL SAFETY DATA SHEET

# SECTION XV REGULATORY INFORMATION

TSCA: All ingredients are listed.

SARA TITLE III: Section 311 and 312: Not listed

### **SECTION XVI OTHER INFORMATION**

HMIS RATINGS: Health=1

Flammability = 0 Reactivity=0

Personal Protective Equipment = B

Hazard rating scale: 0=Minimal, 1=Slight,

2=Moderate, 3=Serious,

4=Severe

Adhesive manufacturer believes the statements, technical information and recommendations contained herein are reliable. They are given without warranty or guarantee of any kind, expressed or implied.