## Identification

Trade Name: Tandus Flooring C-46E Product Class: Premium Floor Primer

# Hazard Identification

Hazardous Ingredients: None HMIS (0=minimal hazard; 4=severe hazard) Health = 1 Flammability = 0 Reactivity = 0 PPE = B

### **Composition/Information on Ingredients**

Description: Synthetic Latex Polymer Dispersion

#### First-Aid Measures

Eye contact may cause irritation. In case of eye contact, flush with water for 10-15 minutes. If irritation persists, consult a physician. Skin Contact: prolonged contact may cause slight irritation of the skin. Wash with soap and water. If swallowed, consult a physician. Inhalation: if symptomatic, move to fresh air. Get medical attention if symptoms occur.

## **Fire-fighting Measures**

Flammable Limits: Non-flammable

Flash Point: >212° F.

Flammability Classification: OSHA: None. DOT: None. Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, and other gases that are common to thermal degradation of organic compounds.

Extinguishing Media: Water, CO<sub>2</sub>, Dry Chemical, Foam. Wear self-contained breathing gear when in confined area. Containers may burst in heat of fire. Material may splatter if temperature exceed 212°F. Use water to cool fire-exposed containers. Dry material can burn.

### Accidental Release Measures

Spills: Cover small spills with inert absorbent, then sweep up and place in waste disposal container. Residual product while still wet, can be cleaned up with warm soapy water. Do not flush unused contents or residue down drains. Contain spill, preventing it from entering sewer lines or waterways.

#### Handling and Storage

Store inside at a temperature of 65°- 85° F. Do not allow product to freeze. Shelf life is one year.

# **Exposure Controls/Personal Protection**

Ventilation: Local ventilation.

Protective Gloves: Recommended.

Eye Protection: Safety glasses.

Hygienic Practices: Wash with soap and water after exposure. Respiratory Protection: Not required with adequate ventilation. Other Protective Equipment: None.

Work Site Environment: Initially there may be a potential adverse impact in indoor air quality within the general work area during the installation process. Therefore you should advise the building manager or other appropriate persons that (1) it will be necessary to establish and maintain adequate ventilation of the work area without causing the entry of contaminates to other parts of the building and (2) persons who are sensitive to odors and/or chemicals should be advised to avoid the work area during this process.





Tandus Flooring C-46E Premium Floor Primer

Date Prepared: 9/10/2009

Tandus Flooring 1000 Vista Drive

Dalton, GA 30721 Information Telephone: 800-241-4902 24 hour Emergency - Chemtrec: 800-424-9300 International Emergency: Call (USA) 202-483-7616

## **Physical and Chemical Properties**

Boiling Point: 212°F
Vapor Density: Same as water.
Evaporation Rate: Same as water.
Appearance and Odor: Milky blue liquid; low odor.
pH: 4.5 - 5.5
Weight per Gallon: 8.8 lbs.
Percent Volatile by Weight: 85% (as water)
Solubility in Water: Dispersible
V.O.C. Content: <1 grams/liter; Meets SCAQMD Rule 1168.</li>

### **Stability and Reactivity**

Conditions to avoid: Excessive heat or cold. Stability: Stable. Incompatibility: None known. Hazardous Polymerization: Will not occur.

## **Toxicological Information**

Not available

## **Ecological Information**

Not available

# **Disposal Considerations**

Dispose of in accordance with Federal, State and Local regulations.

#### **Transport Information**

D.O.T Hazard Class: Unregulated

### **Regulatory Information**

This product does not contain chemicals subject to the reporting requirements of Section 313 of SARA Title III and 40 CFR 372. All components are in compliance with the inventory listing requirements of the U.S. TSCA Inventory. This product does not contain asbestos.

## **Other Information**

Tandus Flooring believes the data set forth herein are accurate as of the date hereof. Tandus Flooring makes no warranty with respect thereto and expressly disclaims all liability for reliance thereon. Such data are offered solely for your consideration, investigation and verification.