

# MSDS SHEET # 1 Ceramic Glazes Lead Bearing

## SECTION 1: CHEMICAL PRODUCT AND COMPANY INFORMATION

Prepared: November 26, 2006  
 Supersedes: All previous  
 Manufacturer: Mayco Colors  
 Division of Coloramics, LLC  
 4077 Weaver Court South  
 Hilliard, Ohio 43026  
 United States of America

### Distributor Contacts:

USA \_\_\_\_\_ Local Phone \_\_\_\_\_  
 EC \_\_\_\_\_ Local Phone \_\_\_\_\_  
 Australia \_\_\_\_\_ Local Phone \_\_\_\_\_

IN CASE OF EMERGENCY PLEASE CONTACT YOUR LOCAL POISON CONTROL CENTER

Prepared by: MSDS department  
 Information Telephone Number: 614-876-1171

### Ceramic Glaze (s): (note See MSDS # 16 for Lead and Copper Bearing Glazes)

Art Glazes AG-201, AG-202, AG-203, AG-207, AG-210, AG-213, AG-240, AG-241, AG-242, AG-244, AG-251, AG-253, AG-254, AG-257, AG-258, AG-261, AG-263, AG-264, AG-291, AG-404, AG-407, AG-408, AG-414, AG-453, AG-454, AG-460, AG-585, AG-601, AG-610, AG-630

Bisque Glazes BG-641

Clear & Dipping Glazes C-100, C-101, C-105, C-109, C-300

Clear Art Glazes CA-110, CA-111, CA-112, CA-113, CA-122, CA-123, CA-124

Exotic Glazes E-101, E-102, E-103, E-105, E-107, E-837, E-850, E-960, E-961, E-965, E-968, E-971

Jungle Gem Crystal Glazes CG-712, CG-716, CG-718, CG-721, CG-722, CG-723, CG-730, CG-750, CG-765, CG-768, CG-772, CG-775, CG-779, CG-783, CG-785, CG-786, CG-788, CG-790, CG-793, CG-795, CG-798, CG-954, CG-958, CG-961

## SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	CAS	ACGIH TLV	OSHA PEL
Leaded Frit	65997-18-4	Lead .15mg/m <sup>3</sup>	Lead .05mg/m <sup>3</sup>
Alumina Silicate	1352-58-7	N/A	N/A
Bentonite	1302-78-9	N/A	N/A

Water	7732-18-5	N/A	N/A
Silica	14808-60-7	0.10mg/M3	0.10mg/M3

### SECTION 3: HAZARDS IDENTIFICATION

Frit contains Lead. Crystalline Silica may also be present (OSHA PEL= 0.1mg/m<sup>3</sup>)  
Route(s) of Entry: Igestion, absorption through the skin is negligible.

Inhalation only if sprayed.

Health Hazards (acute and chronic): Prolonged or repeated inhalation and/or ingestion of lead containing frit may result in lead poisoning. Prolonged inhalation of silica, in excess of TLV, over an extended period of time may result in injury to the lungs. Carcinogenicity: In IARC Supplement 7, inorganic lead compounds are given a 2B rating. This indicates "sufficient evidence" for Carcinogenicity to animals and "inadequate evidence" for Carcinogenicity to humans. California lists lead as a possible carcinogen and requires Prop. 65 warning as required.

### SECTION 4: FIRST AID MEASURES

- If Inhaled: Remove from exposure
- If on skin: Wash skin with soap and water
- If in eyes: Flush eyes with large quantities of water for at least 15 minutes. If irritation persists after washing, contact a physician.
- If swallowed: Dilute by drinking water

### SECTION 5: FIRE FIGHTING MEASURES

#### FIRE AND EXPLOSION HAZARD DATA

Flash Point (method used): N/A

LEL: N/A

UEL: N/A Flammable Limits: N/A

Extinguishing Media: None required, not combustible.

Special Fire Fighting Procedures: None

Unusual Fire and Explosion Hazards: None

### SECTION 6: ACCIDENTAL RELEASE MEASURES

Steps to be taken in case material is released or spilled: Uncontaminated material may be recovered and re-used. If contaminated, scoop, vacuum, or wash into a receptacle for disposal.

Waste Disposal Method: Follow Federal or State and Local regulations for disposal. Lead is listed in US-EPA Code of Federal Regulations 40, Part 261.24. Testing of the waste may be required to determine status under the hazardous waste regulations.

### SECTION 7: HANDLING AND STORAGE

#### PRECAUTIONS FOR SAFE HANDLING AND USE

Engineer Control - None

Work practices- Store away from feed and food. Do not smoke, eat or drink while handling.

Procedure / equipment- None

Procedure for leaks or spills: Uncontaminated material may be recovered and re-used. If contaminated, scoop, vacuum, or wash into a receptacle for disposal.

Waste Disposal Method: Follow Federal or State and Local regulations for disposal. Lead is listed in US-EPA Code of Federal Regulations 40, Part 261.24. Testing of the waste may be required to determine status under the hazardous waste regulations.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Use of the following protective measures are strongly recommended if the glazes are to be applied by spraying.

The Work/Hygienic Practices apply regardless of the method of application. Respiratory Protection (Specify Type): Use a NIOSH approved dust and/or fume respirator as necessary.

Ventilation: Local Exhaust - for spraying

Protective Gloves: N/A

Eye Protection: for spraying

Other Protective Clothing or Equipment: Wear appropriate clean, protective clothing such as, but not limited to, overalls, smocks, and aprons. Work/Hygienic Practices: Food, beverages, and smoking materials should not be in the work area. Hygiene is very important. Wash thoroughly before eating, drinking, smoking, or applying cosmetics.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Various colors

Odor and odor threshold: Negligible

Ph: Not available

Boiling Point: None

Vapor Pressure: NA

Vapor Density: NA

Melting Point: above 1000oF

Specific Gravity (H<sub>2</sub>O= 1): 1.4 to 1.6

Flammable Limits: None

Explosive limits: None

Partition Coefficient: None

Oxidizing Properties: None

Solubility in Water: Negligible

Percent Volatile by Volume: None

Evaporation Rate: None

Freezing point: NA

Flash Point: None

Auto ignition temperature: None

## SECTION 10: STABILITY AND REACTIVITY DATA

Incompatibility (material to avoid): Avoid fumes from firing by venting kiln area.

Stability: Stable (conditions to avoid: N/A)

Hazardous Decomposition or Byproducts: Not available

Hazardous Polymerization: Will not occur

Conditions to avoid: Fumes from firing in kiln. Inhalation of spray.

## SECTION 11: TOXICOLOGY INFORMATION

Hazard to Human: None during normal use. Harmful if inhaled or swallowed.

Lead Bearing Frit (s) - Frit is a fused silicate glass substance.

DO NOT SPRAY APPLY

If glaze is spray applied the following warnings apply: Warning: Contains Quartz.

1. Possible cancer agent based on tests with laboratory animals.
2. Exposure may cause lung damage.
3. Keep out of reach of children; avoid inhalation.

This product contains chemicals known to the State of California to cause cancer. pg 4 of 5

Health Hazards (acute and chronic): Prolonged or repeated inhalation and/or ingestion of lead containing frit may result in lead poisoning. Prolonged inhalation of silica, in excess of TLV, over an extended period of time may result in injury to the lungs. Carcinogenicity: In IARC Supplement 7, inorganic lead compounds are given a 2B rating. This indicates "sufficient evidence" for Carcinogenicity to animals and "inadequate evidence" for Carcinogenicity to humans.

Additional information: Frits are fused silica glass like substances. The bioavailability may be limited because of the physical nature of the frit.

## SECTION 12: ECOLOGICAL INFORMATION

- Mobility: N/A
- Persistence/degradability: N/A
- Bioaccumulation: N/A
- Ecotoxicity: N/A

## SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method: Follow your Federal or State and Local regulations for disposal. Lead is listed in US-EPA Code of Federal Regulations 40, Part 261.24.

Testing of the waste may be required to determine status under the hazardous waste regulations.

Waste from residue/unused product: Can be landfilled according to local regulations. Contaminated packing: Can be landfilled according to local regulations.

## SECTION 14: TRANSPORTATION INFORMATION

UN Number: None for this product.  
For soluble lead UN number is 2291, guide number is 53

## SECTION 15: REGULATORY INFORMATION

Lead and Silica are listed by California , Proposition 65  
Lead and Silica are listed on the IARC, OSHA or NTP carcinogen list.  
All ingredients are on U.S. TSCA / EC / AICS / DSL Inventory.  
See local requirements.

EU Status:

Symbol- None for Frit

For lead compounds;

Repr. Cat 1

R 61- May cause harm to unborn child.

Repr. Cat 3

R62 - Possible risk of impaired fertility

Harmful (xb)

R20/22 - Harmful by inhalation and if swallowed

R33 - Danger of cumulative effects

WHMIS Status : Not Controlled

## SECTION 16: ADDITIONAL INFORMATION

This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of knowledge of COLORAMICS, LLC or obtained from sources believed to be accurate.

COLORAMICS, LLC does not assume any legal responsibility for use or reliance on same. Customers are encouraged to conduct their own tests before using any product. Read the product label.

For more information in AUSTRALIA see web site [www.nohsc.gov.au](http://www.nohsc.gov.au)