



I - PRODUCT IDENTIFICATION AND USE

MSDS ID: 2425

PRODUCT NAME: TASKI P44**USE:** Cleaner and Restorer of Resilient Floors**SUPPLIER:**JohnsonDiversey Canada, Inc.
2401 Bristol Circle
Oakville Ontario, L6H 6P1, Canada**EMERGENCY PHONE:****1-800-668-7171****WHMIS CLASSIFICATION:** B3 D2B**CHEMICAL FAMILY:** Solvent**TRADE NAME / SYNONYMS:** not applicable**CHEMICAL NAME:** not applicable

II - HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENT	% w/w	CAS #	LD50 / LC50	Route / Species
Isopropanol	1-5	000067-63-0	LD50 5045 mg/kg	oral/rat
Petroleum distillates	15-40	064742-47-8	LD50 >5,000 mg/kg	oral/rat

III - HANDLING AND DISPOSAL PROCEDURES

PERSONAL PROTECTIVE EQUIPMENT:**Gloves:** Nitrile or Polyvinyl alcohol**Eye:** safety goggles**Footwear:** not required**Respiratory:** If mists are generated, use NIOSH approved mask**Other:** not applicable**SPECIAL HANDLING PROCEDURES AND EQUIPMENT:** Avoid eye and skin contact. Do not breathe mist or spray.**VENTILATION REQUIREMENTS:** local ventilation**INCOMPATIBILITY (Material to Avoid):** Strong oxidizing agents, heat, open flames, sources of ignition.**SPILL PROCEDURES:** Contain the spill. Do not allow the spilled product to go to drain. Mop up or soak up with absorbent clay for disposal.**WASTE DISPOSAL:** Dispose according to municipal, provincial, and federal regulations.**STORAGE / SHIPPING REQUIREMENT:** Store in a cool dry area in a closed container.

IV - PHYSICAL PROPERTIES

APPEARANCE / ODOUR: Milky white liquid; perfumed**S.G. / BULK DENSITY(g/cc):** 0.917**pH:** 9.5**VAPOUR PRESSURE (mmHg):** not available**VAPOUR DENSITY (air=1):** not available**ODOUR THRESHOLD:** not available**BOILING POINT:** 98°C**FREEZING POINT:** not available**PERCENT VOLATILE:** approx 95%**SOLUBILITY IN WATER:** Miscible**EVAPORATION RATE (water=1):** not available

V - TOXICOLOGICAL PROPERTIES

EFFECTS OF ACUTE EXPOSURE TO MATERIAL:**EYES:** May cause severe irritation.**SKIN:** May cause severe irritation.**INGESTION:** May cause severe irritation.**INHALATION:** May cause severe irritation.**LD50 (calculated):** 15,653 mg/kg**LC50 (calculated):** not available

OTHER TOXIC EFFECTS: TLV - TWA (Isopropyl alcohol): 520 mg/m3.	
EFFECTS OF CHRONIC EXPOSURE TO MATERIAL: Repeated or prolonged contact may result in irritation.	
VI - FIRST AID MEASURES	
EYES:	Flush eyes with plenty of water for at least 15 minutes. Hold eyelids open while rinsing. Contact a physician.
SKIN:	Flush affected area thoroughly with water. If irritation develops, contact a physician.
INGESTION:	Drink large volumes of water . Never give anything by mouth to an unconscious patient. Do not induce vomiting. Contact a physician immediately.
INHALATION:	Remove patient to fresh air. Get medical attention for any breathing difficulty.
VII - FIRE AND EXPLOSION DATA	
FLAMMABLE: Yes, combustible if heated.	
FLASH POINT, °C: 41°C	AUTO IGNITION TEMPERATURE, °C: not avail
EXTINGUISHING MEDIA: Water [] Dry Chemical [x] Carbon Dioxide [x] Foam [x] Other []	
SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus. May flash back. Treat as oil fire.	
HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon.	
EXPLOSIVE SENSITIVITY TO: not applicable	
VIII - REACTIVITY DATA	
STABILITY: Stable [x] Unstable []	
CONDITIONS TO AVOID: Keep away from spark or open flames. Keep away from heat.	
INCOMPATIBILITY (Material to Avoid) : Strong oxidizing agents, open flames, sources of ignition.	
HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon	
REACTIVITY: not dangerously reactive	
IX - MSDS PREPARATION	
SOURCES USED: RTECS, MSDS	PREPARED BY: JohnsonDiversey Canada. Inc. Regulatory Department Institutional Division Phone (905) 829-1200
PREPARATION DATE: April 15, 2003	
<p>Information on this form is furnished in compliance with the Regulations respecting Controlled Products under the Hazardous Products Act and is not to be used for any other purpose, nor is it to be reproduced or published. JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any use of the material if reasonable safety procedures are not adhered to. In addition, JohnsonDiversey Canada assumes no responsibility for injury to any person or property resulting from any abnormal use or theft of the material, even if reasonable safety procedures are followed. Each user assumes the risk in his use of the material and should review the data and recommendations in the specific context of the intended use.</p>	