

Material Safety Data Sheet

Section 1. Chemical Product and Company Identification

Product name NEXT STEP 3 UHS FLOOR COATING

Product use Floor Finish

Product code G082

Date of issue 07/19/12 Supersedes 08/11/09

Emergency Telephone Numbers

For MSDS Information:

Technical Services Group Telephone (780) 453-8100 (Business Hours 8:00am - 5:00pm)

For Medical or Transportation Emergency

CANUTEC (24 Hours)

(613) 996-6666 - Call Collect

Prepared By

Technical Services Group 11627 178th Street Edmonton, Alberta T5S 1N6

Section 2. Hazards Identification

Emergency overview

Do not breathe vapor or mist. Contains material that may cause target organ damage, based on animal data.

NOTE: MSDS data pertains to the product as delivered in the original shipping container(s). Risk of adverse effects are lessened by following all prescribed safety precautions, including the use of proper personal protective equipment.

Acute Effects Routes of Entry Dermal contact. Eye contact.

Eyes May cause eye irritation. Inflammation of the eye is characterized by redness, watering and

itching.

Skin No known significant effects or critical hazards.Inhalation No known significant effects or critical hazards.Ingestion No known significant effects or critical hazards.

Chronic effects Contains material

Contains material which may cause damage to the following organs: kidneys, the reproductive

system, liver, central nervous system (CNS).

Prolonged skin contact may cause dermatitis with drying and cracking of skin.

Additional Information: See Toxicological Information (Section 11)

Section 3. Composition/Information on Ingredients

Name of Hazardous Ingredients	CAS number	% by Weight
2-(2-ETHOXYETHOXY)-ETHANOL; diethylene glycol monoethyl ether, ethoxydiglycol	111-90-0	1 - 5
DIBUTYL PHTHALATE; phthalic acid, dibutyl ester; 1,2-benzenedicarboxilic acid, dibutyl	84-74-2	1 - 5
ester; DBP		
DIPROPYLENE GLYCOL METHYL ETHER; dipropylene glycol monomethyl ether	34590-94-8	1 - 5

Section 4. First Aid Measures

Eye Contact Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and

remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.

Skin Contact Flush affected skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least

10 minutes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly

before reuse.

Inhalation Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide

artificial respiration or oxygen by trained personnel. Get medical attention.

Ingestion If material has been swallowed and the exposed person is conscious, give small quantities of water to drink.

Never give anything by mouth to an unconscious person. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get

medical attention.

Page: 1/4

Section 5. Fire Fighting Measures

Flammable Limits Not available.
Flammability Non-combustible.

Auto-ignition Temperature

Fire-Fighting Procedures Use an extinguishing agent suitable for the surrounding fire. Wear special protective clothing and

positive pressure, self-contained breathing apparatus.

Fire hazard In a fire or if heated, a pressure increase will occur and the container may burst.

Products of Combustion carbon oxides (CO, CO₂) nitrogen oxides (NO, NO₂ etc.)

Explosion hazard Not available.

Section 6. Accidental Release Measures

Spill Clean up Put on appropriate personal protective equipment (see section 8). Stop leak if without risk. Move containers

from spill area. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in

an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Section 7. Handling and Storage

Handling Put on appropriate personal protective equipment (see section 8). Do not get in eyes or on skin or clothing. Do not

breathe vapor or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be

hazardous. Do not reuse container. Wash thoroughly after handling.

Storage Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible

materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Keep out of the reach of

children.

Section 8. Exposure Controls/Personal Protection

Product name Exposure limits

2-(2-ethoxyethoxy)ethanol CA Ontario Provincial (Canada, 7/2010).

TWA: 165 mg/m³ 8 hour(s). TWA: 30 ppm 8 hour(s).

(2-methoxymethylethoxy)propanol CA Alberta Provincial (Canada, 4/2009). Absorbed through skin.

8 hrs OEL: 100 ppm 8 hour(s). 15 min OEL: 909 mg/m³ 15 minute(s). 8 hrs OEL: 606 mg/m³ 8 hour(s). 15 min OEL: 150 ppm 15 minute(s).

CA British Columbia Provincial (Canada, 9/2010). Absorbed through skin.

TWA: 100 ppm 8 hour(s). STEL: 150 ppm 15 minute(s).

CA Quebec Provincial (Canada, 6/2008). Absorbed through skin.

TWAEV: 100 ppm 8 hour(s). TWAEV: 606 mg/m³ 8 hour(s). STEV: 150 ppm 15 minute(s). STEV: 909 mg/m³ 15 minute(s).

CA Ontario Provincial (Canada, 7/2010). Absorbed through skin.

STEL: 909 mg/m³ 15 minute(s). STEL: 150 ppm 15 minute(s). TWA: 606 mg/m³ 8 hour(s). TWA: 100 ppm 8 hour(s).

Personal Protective Equipment (PPE)

Hands and

Body

Eyes Recommended: Safety eyewear should be used when there is a

likelihood of exposure. Safety glasses.

Recommended: For prolonged or repeated handling, use the

following type of gloves: Neoprene Nitrile Rubber

Respiratory Recommended: Use with adequate ventilation. Provide exhaust ventilation or

other engineering controls to keep the airborne concentrations of vapors below

their respective occupational exposure limits.

Page: 2/4

Product code G082 Material Safety Data Sheet Product Name NEXT STEP 3 UHS FLOOR COATING

Section 9. Physical and Chemical Properties

Physical State Liquid. Color White. Translucent. pH 8.2 - 8.6 Odor Not available.

Boiling Point100°C (212°F)Vapor Pressure Not applicable.Specific Gravity1.03Vapor Density Not applicable.

Solubility Easily soluble in the following materials: cold water **Evaporation Rate** 1 (Water = 1)

and hot water.

Freezing Point 0 VOC (Consumer) 3.8 %

Section 10. Stability and Reactivity

Stability and Reactivity The product is stable.

Incompatibility Reactive or incompatible with the following materials: oxidizing materials.

Hazardous Polymerization Will not occur.

produced.

Section 11. Toxicological Information

Carcinogenicity Ingredients: Not listed as carcinogen by OSHA, NTP or IARC.

Acute Toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2-(2-ethoxyethoxy)ethanol	LC50 Inhalation Vapor	Rat	>200 mg/L	1 hours
, , ,	LD50 Dermal	Rabbit	9143 mg/kg	-
	LD50 Oral	Mouse	6301 mg/kg	-
	LD50 Oral	Rat	7500 mg/kg	-
	LD50 Oral	Rat	10502 mg/kg	-
(2-	LD50 Dermal	Rabbit	13000 mg/kg	=
methoxymethylethoxy)propanol				
	LD50 Oral	Rat	5220 mg/kg	-

Section 12. Ecological Information

Environmental Effects No known significant effects or critical hazards.

Aquatic Ecotoxicity

2-(2-ethoxyethoxy)ethanol - Acute LC50 3340000 Daphnia - Water flea - 48 hours

ug/L Fresh water Daphnia magna -

Neonate - 0 to 24 hours

- Acute LC50 6010000 Fish - Channel catfish - 96 hours ug/L Fresh water Ictalurus punctatus -

0.72 g

Section 13. Disposal Considerations

Waste Information

Waste must be disposed of in accordance with applicable regulations. Consult your local or regional authorities for additional information.

Waste Stream Code: - (Not applicable.)

Classification: - (Non-hazardous waste)

Section 14. Transport Information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
TDG Classification	Not regulated.	-	-	-		-
IMDG Class	Not available.	Not available.	Not available.	-		-

NOTE: DOT classification applies to most package sizes. For specific container size classifications or for size exceptions, refer to the Bill of Lading with your shipment. Limited Quantity: Small quantities of controlled goods are not regulated as Dangerous Goods according to TDG regulations.

PG*: Packing group

Product code G082 **Material Safety Data Sheet** Product Name NEXT STEP 3 UHS FLOOR COATING

Section 15. Regulatory Information

Canada

Class D-2B: Material causing other toxic effects (Toxic). WHMIS (Canada)

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

Section 16. Other Information

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution.

Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.