

CARMEL GROUP INC.

SAFETY DATA SHEET

Section 1 – PRODUCT AND COMPANY IDENTIFICATION

Product Name Chalk-Line Powder Red	Product Code IC20109, IC20209, IC20309, & IC20409 (See p. 8)
---------------------------------------	---

Product Use
Marking chalk to use in chalk-line reels.

Manufacturer / Supplier Carmel Group Inc. 10220 Armand Lavergne, Montréal, Québec, Canada, H1H 3N4	Phone : 514-270-5377 Fax : 514-270-2025 Internet : www.carmelindustries.com
---	---

Emergency Phone Number (USA & Canada)
CHEMTREC (USA) : 800-424-9300 CHEMTREC (International) : 1-703-527-3887
CANUTEC (Canada) : 613-996-666

SDS Issue Date : December 8, 2016

MSDS Version : 2.01

Section 2 – HAZARD IDENTIFICATION

2.1 Emergency Overview

Appearance/Odor : Red solid powder.

Description : Dust from this product can be toxic if their inhale in large quantity or in small quantity for a long period.

2.2 OSHA & WHMIS Status

The product is an hazardous material as defined by U.S. OSHA HCS (29 CFR 1910.1200). The product is considered to be hazardous material as defined by Canadian WHMIS Controlled Product Regulation (CPR). It is classified under Class D2A (Class D Poisonous and infectious Materials : Very toxic material causing other toxic effects).

2.3 Potential Health Effects (See Section 11 for more information)

Likely Route of Exposure
Inhalation, skin and/or eye contact of the powder during manipulation.

Eye : May cause mild, transient irritation.

Skin : May cause mild, transient irritation.

Ingestion : No known irritation. Do not ingest.

Inhalation : Potential irritation, may be harmful if inhaled. Chronic exposure can be toxic.

Medical Condition Aggravated by Exposure
None known.

Target Organs : Eyes, skin, respiratory system.

Carcinogenicity (NTP, IARC and OSHA)

Breathable Silica (CAS#14808-60-7) is considered a carcinogen by IARC (Group 1 carcinogen), ACGIH (A2 - Suspected Human Carcinogen) and is listed in the NTP list of known human carcinogen.

2.3 Potential Environmental Effects (See Section 12 for more Information)

None known.

Section 3 – COMPOSITION/INFORMATION ON INGREDIENTS

Component	Cas#	%byWt	Classification and Rphrases
Limestone	1317-65-3	98,1%	R36, S26 and S39
Iron Oxide (III)	1309-37-1	20%	Not available
Silicone Dioxide	14808-60-7	1,9%	R23 and S24/25

Section 4 – FIRST AID MEASURES

4.1 First Aid Procedures

Eye : If this chemical contacts the eyes, immediately wash the eyes with large amounts of water, occasionally lifting the lower and upper lids. Get medical attention immediately.

Skin : Wash skin with water & soap or industrial hand cleaner.

Ingestion : Administer large quantities of water. Do not induce vomiting. Call a physician.

Inhalation : Remove individual to a well ventilated area for fresh air and call a physician to attend to the injury.

4.2 Note to Physicians

None.


Section 5 – FIRE FIGHTING MEASURES

5.1 Flammable Properties (See Section 9 for more Information)

Will not burn if involved in a fire, but will decompose at high temperature (825°C / 1520°F).

NFPA Rating

0 = Minimal
1 = Slight hazard
2 = Moderate Hazard
3 = Serious Hazard
4 = Severe Hazard



5.2 Extinguishing Media

5.2.1 Suitable Extinguishing Media
Not Available.

5.2.2 Unsuitable Extinguishing Media
None.

5.3 Protection of Fire fighters

5.3.1 Specific Hazards Arising from the Chemical
High temperature can produce carbon dioxide and calcium oxide (quicklime).

5.3.2 Protective Equipment and Precautions for Fire-fighters

Keep people away from fire and smoke, wear full fire fighting turn-out gear and respiratory protection.

Section 6 – ACCIDENTAL RELEASE MEASURES

6.1 Personal Precautions

Use recommended personal protective equipment for solid product (See Section 8 for more Information).

6.2 Environmental Precautions

Use physical barrier to prevent spilled material from entering waterways.

6.3 Methods for Containment

No containment needed for solid state. Any physical barrier will stop the spreading of the dust.

6.4 Methods for Clean-Up

For large spill you may want to use to sweep up a control sweeping compounds or vacuum with H.E.P.A. filter. For small quantity you just sweep up.

6.5 Other Information

None

Section 7 – HANDLING AND STORAGE

7.1 Handling

Handle as a fragile material. Keep containers closed to prevent spills and wash thoroughly exposed body part after using. See section 8.3 for personal protective equipment (PPE).

7.2 Storage

Normal precaution should be followed in handling and storage. Store in a dry & cool place.

Section 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Exposure Guidelines

Hazardous Ingredients	CAS#	Exposure Limits (ppm)					
		OSHA		ACGIH		NIOSH	
		TWA	STEL	TWA	STEL	TWA	STEL
Limestone	1317-65-3	15	None	10	None	10	None
Iron Oxide (III)	1309-37-1	10	None	5	None	5	None
Silicone Dioxide	14808-60-7	0.1	None	0.05	None	0.05	None


8.2 Engineering Controls

Not needed for normal use.

8.3 Personal Protective Equipment (PPE)**8.3.1 Eye / Face Protection**

Protective glass.				
8.3.2 Skin Protection Latex or vinyl glove.				
8.3.3 Respiratory Protection Dust mask with the NIOSH certification of N95 Particulate Respirator.				
8.3.4 General Hygiene Considerations Wash exposed part with soap.				
Section 9 – PHYSICAL AND CHEMICAL PROPERTIES				
Appearance Red powder		Odor None		Physical state Solid @ 25°C/77°F
pH Not Available		Vapour pressure (mm Hg) 0.0 mm Hg (approx)		Vapour Density Not Available
Boiling point Decomposes		Melting point 825-1338°C/1517-2442°F (Decomposes)		Flash point Not Available.
Autoignition Temperature Not Available		Decomposition Temperature Not Available		Specific Gravity (H ₂ O = 1) 2.95 - 3.08
Evaporation Rate Not Available		Coefficient of water/oil distribution Not Available		Odor Threshold (ppm) Not Determined.
Relative Density > 1g/ml		Solubility-Water 0.0015 g/ 100 ml		Partition Coefficient n-octanol/water Not Available
Section 10 – STABILITY AND REACTIVITY DATA				
10.1 Chemical Stability				
Stable. Hazardous polymerisation will not occur.				
10.2 Conditions to Avoid				
Reacts with acids and acidic salts to generate gaseous carbon dioxide with effervescence (bubbling). The reaction with concentrated solutions of acids is rapid and exothermic. The effervescence can create extensive foaming. Ignites on contact with fluorine.				
10.3 Incompatible Materials				
Incompatible with acids, alum, ammonium salts, fluorine, magnesium.				
10.4 Hazardous Decomposition Products				
High temperature (825°C / 1520°F) can produce carbon dioxide and calcium oxide (quicklime).				
10.5 Possibility of Hazardous Reactions				
None Known.				
Section 11 – TOXICOLOGICAL INFORMATION				
11.1 Acute Effects				
Hazardous Ingredients	CAS#	%	OralLD ₅₀	DermalLD ₅₀
None	None	Nil	None	None

Inhalation : Chronic exposure to dust can be harmful and even toxic.
Eye Irritation : Possible irritant for the eyes.
Skin Irritation : None Known.
Sensitization : None Known.
11.2 Chronic Effects
Carcinogenicity : Breathable Silica (CAS#14808-60-7) is considered a carcinogen by IARC (Group 1 carcinogen), ACGIH (A2 - Suspected Human Carcinogen) and is listed in the NTP list of known human carcinogen.
Mutagenicity/Teratogenicity : Not listed.
Reproductive Effects : No effects known.
Development Effects : No effects known.
Section 12 – ECOLOGICAL INFORMATION
Ecotoxicity : Not determined.
Persistence/Degradability : Not determined.
Bioaccumulation/Accumulation : Not determined.
Mobility in Environmental Media : Not determined.
Other Adverse Effect : None known.
Section 13 – DISPOSAL CONSIDERATION
Waste Disposal : Dispose as industrial waste in accordance with appropriate Federal, State and local regulation.
Section 14 – TRANSPORT INFORMATION
14.1 Basic Shipping Description
US DOT : Not regulated.
14.2 Additional Information
IMO : Not regulated.
Canadian TDG : Not regulated.
ICAO : Not regulated.
IATA : Not regulated.
Section 15 – REGULATORY INFORMATION
15.1 Global Inventory Status
TSCA (United States) : All ingredients of this product are listed on the U.S. Environmental Protection Agency (EPA) , (TSCA) Toxic Substances Control Act and Chemical Substance Inventory.
DSL (Canada) : All ingredients of this product are listed on the Canadian (EPA) Canadian

Environmental Protection Act.	
EINECS (EU) : All ingredients of this product are listed on the European Inventory of Existing Chemical Substances (EINECS).	
AICS (Australia) : All ingredients of this product are listed on the Australian Inventory of Chemical Substances (AICS).	
15.2 SARA Status	
Hazard Class(es) Section (311/312) : None.	
Section 313 Toxic Chemicals : None.	
Section 302 Extremely Hazardous Substances (EHS) : None.	
15.3 US State Regulations	
Limestone (1317-65-3) appear on the Massachusetts and Minnesota Right-To-Know Substance List as well as the Pennsylvania Hazardous Substance list. Silicone Dioxide (14808-60-7) appear on the California, Massachusetts, Minnesota and New Jersey Right-To-Know Substance List as well as the Pennsylvania Hazardous Substance list and the California Safe Drinking Water and Toxic Enforcement Act (Prop. 65) Substances List.	
15.4 WHMIS Status & Classifications	
The product is considered to be hazardous material as defined by Canadian WHMIS Controlled Product regulation(CPR). It is classified under Class D2A (Class D Poisonous and infectious Materials : Very toxic material causing other toxic effects). Silicone Dioxide (14808-60-7; <2%) appear on the Canadian WHMIS Ingredient Disclosure List.	 D2A
15.5 OSHA Status & Classifications	
The product is an hazardous material as defined by U.S. OSHA HCS (29 CFR 1910.1200).	
Section 16 – OTHER INFORMATION	
MSDS of the product is classified in accordance with all the required information for his hazard criteria under the Health Communication Standards (HCS) of the U.S. OSHA and all the required information for his hazard criteria under the Controlled Products Regulations (CPR) of the Canadian WHMIS. MSDS of the product is made following the Z400.1-2003 standards of the ANSI.	
Prepared By : Federico Segovia	

The information contained in this document is derived from data supplied to Carmel Group by the manufacturers or distributors of the raw materials combined to form this product. However, Carmel Group makes no representations as to its completeness or accuracy. To the best of our knowledge all hazards have been noted for the intended use of the product and, since Carmel Group cannot control conditions of use, the end user is obliged to determine the conditions permitting safe use of the product. In no event will Carmel Group be responsible for damage of any nature whatsoever resulting from the use of or reliance upon the information contained herein.

CARMEL GROUP INC.

CHALK-LINE POWDER RED PRODUCT LIST

Product code	Product Description
IC20109	Chalk-Line Powder Red 8 oz Container
IC20209	Chalk-Line Powder Red 5 lbs Container
IC20309	Chalk-Line Powder Red 25 lbs Container
IC20409	Chalk-Line Powder Red 50 lbs Container