KLEEN-FLO TUMBLER IND	MATERIAL SAFETY DATA SHEET			PAGE 1			
SECTION I-MATERIAL IDEN	NTIFICATION AND	USE					
Material Name/Identifier:	TEF-Lube 2000		Stock No.			813	
Manufacturer's Name:	Kleen-Flo Tumbler Industries Ltd		Street Address:			75 Advance Blvd.	
City:	Brampton		Province:			Ontario	
Postal Code:	L6T 4N1		Emergency Phone #:		CANUTEC:-	613-996-6666 (24HR)	
Chemical Name:	N/Ap (Mixture)		Chemical Family:			N/Ap (Mixture)	
Chemical Formula:	N/Ap (Mixture)		Trade Names & Synonyms:		ıs:	TEF-Lube 2000	
Material Use:	Lubricating Oil (aerosol)		Molecular Weight:		N/Ap (Mixture)		
SECTION II-HAZARDOUS IN	NGREDIENTS OF M	<u> </u>	T		T		
Hazardous		Approximate		LD50		LC50	
Ingredients	C.A.S.	Concentration	Species &			Species & Route	
Lt.aliphatic hydrocarbon solver		1 - 5	N/Av.		N/Av.		
Heptane	142-82-5	30 -60	N/Av.		N/Av.		
2-Methyl Cyclohexane	108-87-2	1-5	N/Av.		N/Av.		
Naphthenic oil	64742-63-8	1-5	N/Av.		N/Av. N/E		
Petrolatum	8009-03-8 106-97-8	5- 10 10-30%	N/Av. N/Av.		N/E 142,500 ppm (4hr) rat-inhal		
Butane	74-98-6	5-10%		5000mg/kg dermal-rabbit N/E		(4nr) rat-innai	
Propane SECTION III-PHYSICAL DAT			>5000mg/kg	dermai-rabbi	N/E		
SECTION III-I II I SICAL DA	IA FOR MATERIA	<u>u</u>					
Physical State:	Oily liquid	Odour/Appearance: Solvent Odour		our, Clear Am	ber Oily liquid		
Specific Gravity:	0.69	Odour Threshold(p.p.					
Boiling Point:	-18 to 81oC	Evaporation Rate (B.A					
Freezing Point:	N/E	Solubility in Water:		None			
% Volatile(by volume):	78%	Vapour Pressure (mm					
Vapour Density(Air=1):	>1	Coefficient of Water/O	il Distribut: N/E				
рН	N.Ap.						
SECTION IV-FIRE AND EXP	LOSION HAZARD	OF MATERIAL					
Flammability Yes/No	Extremely flammak	If yes under which conditions?: open flame, sparks, fire				re	
Auto Ignition Temperature:	N/E	Means of Extinction: Water fog, dry chemical, carbon dioxide, foam					
Flashpoint and Method:	< - 18 °c Lowest kn	Hazardous Combustion Product.: Carbon monoxide, carbon					
				dioxide, black fume and smoke.			
Upper Flammable limit	9.5 %vol	Lower Flammable Limit(% by volume): 1.0					
Explosion Data:	Sensitivity to Mecha	Sensitivity to Static Discharge: N.Ap.					
SECTION V-REACTIVITY D.	ATA						
Chemical Stability Yes/No: Yes			If NO under which conditions? N.Ap.				
Incompatibility to Other Substances Yes/No:		Yes	If so which ones? Strong oxidizers,				
Reactivity and under what conditions?		N/Av.					

Carbon dioxide, carbon monoxide, hydrocarbon fumes, smoke.

N/Av.: not available

N.Ap.: not applicable

Hazardous Decomposition Products:

N/E: not established

Material Name/Identifier:	TEF-Lube 2000 Stock No. 813 PAGE 2					
SECTION VI-TOXICOLOGI	CAL PROPERTIES OF PRODUCT					
Route of Entry:	SKIN CONTACT -x-SKIN ABSORPTIONEYE CONTACT -x-INHALATION -x-INGESTION					
Effects of Acute Exposure:	May cause skin, eye, respiratory system irritation, dizziness, nausea, nervous system depression.					
•	Redness, itching, burning sensation may indicate excessive exposure to eyes or skin.					
Effects of Chronic Exposure:	Extreme overexposure may result in unconsciousness and possibly death.					
-	Rports have associated repeated, prolonged	l overexposure to solvents with permaner	nt brain and nervous system damag			
LD 50 of Product:	N/E	LC 50 of Product: N/E				
Irritancy of Product:	May cause severe eye irrit. & skin rash	Exposure Limits of Product:	N/E			
Sensitization of Product:	N/E	Toxicologically Synergistic Materials:	N/Av.			
CARCINOGENICITYRE	PRODUCTIVE EFFECTSTERATOGENI		None Known			
	is an IARC, NTP OR OSHA listed carcinoger					
SECTION VII-PREVENTIVE						
Personal Protective Equipmen						
Gloves(specify):	Chemical resistant gloves Eye(specify): Safety goggles					
Respiratory (specify):	NOISH approved Organic Vapor mask Clothing: Apron					
Respiratory Protection:	If used indoors or on a continuous basis, use of NIOSH approved cartridge type respirator is recommended					
Engineering Controls:	Local or mechanical exhaust ventilation is required.					
Leak and Spill Procedure:	Contain& Collect. Use inert absorbent to soak up material. Prevent from entering waterways.					
Leak and Spin 1 foccure.						
Waste Disposal:	Remove all ignition sources, use non sparking tools. Dispose at approved waste disposal service site as per local, provincial or federal regulation.					
Storage Requirements:	Keep away from heat, sparks or open flame. Store at temperature below 40°C. Keep container closed when not in use					
Handling Procedures and	Avoid skin, eye contact. Do not inhale or ingest. Do not puncture or incinerate container even when it's empty. Handle with case Veen every from children					
Equipment:	Handle with care. Keep away from children.					
DSL listing	All components are listed on the inventory.					
NFPA30B/CNFC 3.3.5	Level 2					
TDG Classification:	Classified as "Consumer Commodity"					
WHMIS Classification: SECTION VIII-FIRST AID M	Complies with CCCR-2001 Regulation TEASURES					
Eye:	Wash with water for at least 15 minutes. Seek immediate medical help if discomfort persists.					
Skin:	Wash with soap & water. Remove severely contaminated clothes. If rash persists, seek med. help.					
Inhalation:	Move patient to fresh air and restore breathing if required. See doctor if discomfort persist.					
Ingestion:	DO NOT INDUCE VOMITING. Get prompt medical attention.					
SECTION IX-PREPARATIO	N DATE OF M.S.D.S.					
Additional Info/Comments:		Sources Used: Supplier's data.				
Phone Number:	(905) 793-4311	Prepared By: Quality Control Laboratory				
Date Prepared:	May 8 2012 Kleen-Flo Tumbler Industries Limited					
Tring or	HEET CHDEDCEDEC AND OTHER M.C.D.C.	DDEVIOUSLY DDEPAREN				
N/E: not established	HEET SUPERSEDES ANY OTHER M.S.D.S N.Ap.: not a		N/Av.: not available			
1 1/2. Hot complished	11.лр пот а	Phicasic	1 1/1 1 1 1 1 1 Ut a ranavic			